

Dynasty® 400 and 800

TIG/Stick Welding
Power Source



QUICK SPECS

Industrial Applications

Precision fabrication
Heavy fabrication
Pipe and tube fabrication
Aerospace
Aluminum ship repair
Anodized aluminum fabrication

Processes

AC/DC TIG (GTAW)
Pulsed TIG (GTAW-P)
Stick (SMAW)
Air carbon arc (CAC-A)
400: 1/4 in. maximum
800: 3/8 in. maximum

Input Power 208–600 V, 3-phase or 1-phase power

Amperage Range 400: 3–400 A
800: 5–800 A

Rated Output 400: 300 A at 32 V, 60% duty cycle
800: 600 A at 44 V, 60% duty cycle

Net Weight 400: 126 lb. (57 kg)
800: 201 lb. (91 kg)

Reimagined for Your Pursuit of Perfection.

Experience unfailing precision arc performance paired with a state-of-the-art, user-friendly interface that puts advanced capabilities at your fingertips. Dynasty TIG power sources help minimize error and achieve high-precision welds every time, making the best welders even better.



Easy-to-understand interface with 7-inch LCD display.

- Ensures proper machine setup and parameter selection
- Informative on-screen explanations and dynamic images enhance the parameter selection process



**Dynasty 400
Machine only**



**Dynasty 400
Wireless Complete**

QUIETPULSE™

Activate QuietPulse by selecting sine or triangular waveshape to reduce audible noise.

Blue Lightning™ provides more consistent high-frequency (HF) arc starts and greater reliability compared to traditional arc starters.

Lift-Arc™ provides AC or DC arc initiation without the use of high frequency.

AUTO-LINE™ TECHNOLOGY

Allows for any input voltage hookup (208–600 V) with no manual linking, providing convenience in any job setting. Ideal solution for dirty or unreliable power.

Program memory allows easy naming, saving and recalling of favorite weld settings.

- Deliver more productivity by eliminating the need to manually set the parameters
- Deliver consistent quality by welders of all skills

Pro-Set™ eliminates the guesswork when setting weld parameters.

Locks and limits. Provides control of weld parameter ranges minimizing deviation from the welding procedure specification (WPS).

USB. Front panel port provides the ability to easily update software, back-up settings and transfer saved weld programs from one unit to the next.

Visit MillerWelds.com/TIGSoftware for the latest software updates and expansions.

Cooler Power Supply (CPS) is a dedicated-use receptacle for the Coolmate™ PRO 4.

Cooler-On-Demand™ feature operates the auxiliary cooling system only when needed, reducing noise, energy use, and airborne contaminants pulled through the cooler.



Power source is warranted for three years, parts and labor.



Miller Electric Mfg. LLC
An ITW Welding Company
1635 West Spencer Street
P.O. Box 1079
Appleton, WI 54912-1079 USA

Equipment Sales US and Canada
Phone: 866-931-9730
International Phone: 920-735-4554

MillerWelds.com



Weld Process Features

AC TIG

Balance control provides adjustable oxide removal which is essential for creating the highest quality aluminum welds.

Frequency controls the width of the arc cone and can improve directional control of the arc.

AC Waveforms



Advanced square provides a fast freezing puddle, deep penetration and fast travel speeds.



Soft square for a soft buttery arc with maximum puddle control and good wetting action.



Sine for customers that like a traditional arc. Quiet with good wetting.



Triangular reduces the heat input and is good on thin aluminum. Fast travel speeds.

Independent amplitude/amperage control allows EP and EN amperages to be set independently to precisely control heat input to the work and electrode.

DC TIG

Exceptionally smooth and precise arc for welding exotic materials.

Pulse. Pulsing can increase puddle agitation, arc stability and travel speeds while reducing heat input and distortion.

Pulse Waveforms



Square provides a fast freezing puddle for ultimate arc control.



Sine produces a reduced audible sound and provides a more fluid puddle that is good for overlaying applications.



Triangular provides a quick-forming puddle while further reducing heat for thin materials.

QuietPulse™. Activate QuietPulse by selecting sine or triangular waveshape to reduce audible noise.

AC/DC Stick

DIG control allows the arc characteristics to be changed for specific applications and electrodes. Lower the DIG setting for smooth running electrodes like E7018 and increase the DIG setting for stiffer, more penetrating electrodes like E6010.

Hot Start™ adaptive control provides positive arc starts without sticking.

AC frequency control adds stability for smoother welds when AC stick welding.

Stick-Stuck detects if the electrode is stuck to the part and turns the welding output off to safely and easily remove the electrode. Menu selectable.

Specifications (Subject to change without notice.)



MODEL	INPUT POWER	WELDING AMPERAGE RANGE	RATED OUTPUT	AMPS INPUT AT RATED OUTPUT, 50/60 HZ 208 V 230 V 400 V 460 V 600 V KVA KW							MAX. OPEN-CIRCUIT VOLTAGE	DIMENSIONS	NET WEIGHT
Dynasty 400	3-phase	3–400 A	250 A at 30 V, 100% duty cycle	28	26	14	13	10	10.3	9.8	75 VDC (10–15 VDC*)	H: 24.125 in. (613 mm) W: 13.875 in. (352 mm) D: 24.313 in. (618 mm) with TIGRunner® H: 43.125 in. (1,095 mm) W: 23.125 in. (587 mm) D: 41.625 in. (1,057 mm)	126 lb. (57 kg) with TIGRunner® 246 lb. (112 kg)
			300 A at 32 V, 60% duty cycle	36	33	19	16	12	13.1	12.5			
	1-phase	3–400 A	200 A at 27.2 V, 100% duty cycle	39	35	19	17	12	8.2	7.5			
			250 A at 29 V, 60% duty cycle	52	47	26	22	16	10.9	9.9			
Dynasty 800	3-phase	5–800 A	500 A at 40 V, 100% duty cycle	73	66	37	32	24	26	25	75 VDC (10–15 VDC*)	H: 34.25 in. (870 mm) W: 13.875 in. (352 mm) D: 24.313 in. (618 mm) with TIGRunner® H: 52.625 in. (1,337 mm) W: 23.125 in. (587 mm) D: 41.625 in. (1,057 mm)	201 lb. (91 kg) with TIGRunner® 320 lb. (145 kg)
			600 A at 44 V, 60% duty cycle	96	86	48	42	32	35	33			
	1-phase	5–800 A	400 A at 34 V, 100% duty cycle	98	88	48	41	31	20	19			
			500 A at 40 V, 60% duty cycle	136	122	66	56	42	28	26			

*Sense voltage for low OCV stick and Lift-Arc™ TIG.

Certified by Canadian Standards Association to both the Canadian and U.S. Standards.


All CE models conform to the applicable parts of the IEC 60974 series of standards.

Performance Data

MODEL	INPUT POWER	TIG (GTAW) DUTY CYCLE	STICK (SMAW) DUTY CYCLE	AC TIG MATERIAL THICKNESS RANGE	DC TIG MATERIAL THICKNESS RANGE	STICK ELECTRODE MAXIMUM DIAMETER	CARBON ARC GOUGING (CAC-A) MAXIMUM	GENERATOR REQUIREMENT
Dynasty 400	3-phase	400 A, 20% 300 A, 60% 250 A, 100%	400 A, 20% 300 A, 60% 250 A, 100%	.015–5/8 in. (0.38–15.9 mm)	.012–5/8 in. (0.3–15.9 mm)	6010: 1/4 in. (6.4 mm) 7018: 1/4 in. (6.4 mm) 7024: 1/4 in. (6.4 mm)	1/4 in. (6.4 mm)	20 kW
	1-phase	300 A, 20% 250 A, 60% 200 A, 100%	300 A, 20% 250 A, 60% 200 A, 100%					
Dynasty 800	3-phase	800 A, 20% 600 A, 60% 500 A, 100%	700 A, 20% 600 A, 60% 500 A, 100%	.020–1 in. (0.5–25.4 mm)	.020–1 in. (0.5–25.4 mm)	6010: 1/4 in. (6.4 mm) 7018: 1/4 in. (6.4 mm) 7024: 1/4 in. (6.4 mm)	3/8 in. (9.5 mm)	50 kW
	1-phase	500 A, 60% 400 A, 100%	500 A, 60% 400 A, 100%					

Dynasty® 400 and 800 Control Panel

1. Color LCD Display
2. Soft Keys
(multiple functions depending on screen displayed)
3. Control Knob
(adjusts amperage or parameter values depending on mode)
4. Home Button
5. Program Button
6. USB Port



Amperage

TIG AC	400: 3–400 A**	800: 5–800 A**
TIG DC	400: 3–400 A**	800: 5–800 A**
Stick	400: 3–400 A	800: 5–800 A

Process

AC TIG HF, DC TIG HF,
AC TIG Lift-Arc™, DC TIG Lift-Arc™,
AC Stick, DC Stick,
Carbon Arc Gouge, Hotwire

Tungsten (inch)

.020, .040, 1/16, 3/32, 1/8, 5/32, 3/16 inch, General
(.05, 1.0, 1.6, 2.4, 3.2, 4.0, 4.8 mm)

Trigger

Remote Standard: Foot, Finger, Pushbutton
Sequencer: Pushbutton Hold (2T), 3T 4T,
4TE, 4TL, 4TM

Pulse

Pulses per Second*	DC: 0.1–5,000 pps AC: 0.1–500 pps
Peak Time*	5–95%
Background Amps*	5–95%
DC Pulse Waveshape:	Square, Sine, Triangular

AC Waveshape

Balance*	Ball: 30–99% EN
Frequency*	20–400 Hz
Waveshape	Advanced Square, Soft Square, Sine, Triangular
Independent	EN Amperage: 400: 3–400 A** 800: 5–800 A** EP Amperage: 400: 3–400 A** 800: 5–800 A** EN Waveshape: Advanced Square, Soft Square, Sine, Triangular EP Waveshape: Advanced Square, Soft Square, Sine, Triangular
Commutation	Low, High

Sequencer Control

Initial Amps AC	400: 3–400 A**	800: 5–800 A**
Initial Amps DC	400: 3–400 A**	800: 5–800 A**
Initial Time	0.0–25.0 seconds	
Initial Slope	0.0–50.0 seconds	
Weld Time	0.0–999 seconds	
Final Slope	0.0–50.0 seconds	
Final Amps AC	400: 3–400 A**	800: 5–800 A**
Final Amps DC	400: 3–400 A**	800: 5–800 A**
Final Time	0.0–25.0 seconds	

Preflow

0.0–25.0 seconds

Postflow

Auto/Off–50 seconds

DIG*

Off–100%

Hot Start™

On, Off

Stick-Stuck

On, Off

OCV

Normal, Low

Programs

1–99 (user defined program names)

Locks and Limits

Individual Parameters

Languages

English, Spanish, French, German, Italian,
Dutch, Swedish, Polish

*Pro-Set parameter selectable. **Amperage range is tungsten size dependent.

Dynasty® 400 and 800 Models/Packages

Machines and Preconfigured Water-Cooled Packages —

Order machine only or use a single stock number to order a complete preconfigured system



Machine Only		TIGRunner® Package		Complete Package
Dynasty 400	907950	Dynasty 400	907950001	Dynasty 400 with Wireless Foot Control
Dynasty 400, CE	907950002	Dynasty 400, CE	907950003	951000263
Dynasty 400 comes with:		Dynasty 400 TIGRunner comes with:		Complete package includes TIGRunner at left, plus:
• 8 ft. power cord (no plug)		• 8 ft. power cord (no plug)		• Coolant (4 one-gallon bottles)
• Two 50 mm Dinse-style connectors		• Coolmate™ PRO 4		• W-375 torch kit (see page 6 for contents)
		(quick connect model on CE TIGRunner)		• Wireless foot control
Dynasty 800	907951	Dynasty 800	907951001	Dynasty 800 with Wireless Foot Control
Dynasty 800, CE	907951002	Dynasty 800, CE	907951003	951000264
Dynasty 800 comes with:		Dynasty 800 TIGRunner comes with:		Complete package includes TIGRunner at left, plus:
• Two thread-lock connectors		• Two thread-lock connectors		• Coolant (4 one-gallon bottles)
• One thread-lock water-cooled connector		• One thread-lock water-cooled connector		• W-400 (WP-18SC) torch kit
		• Coolmate™ PRO 4		(see page 6 for contents)
		(quick connect model on CE TIGRunner)		• Wireless foot control
		• Runner™ cart		

Build a Water-Cooled Package — select desired stock number for each step



Step 1 • Select Dynasty TIGRunner® and Coolant		Step 2 • Select Remote Control		Step 3 • Select Torch Kit	
Dynasty 400 TIGRunner	907950001	Wireless Foot	301580	W-375 Kit	301268
Dynasty 400 TIGRunner, CE	907950003	RFCS-14 HD Foot	301589	(recommended for 400 model)	
Dynasty 800 TIGRunner	907951001	RCC-14 E/W Fingertip	151086	W-400 (WP-18SC) Kit	300186
Dynasty 800 TIGRunner, CE	907951003	RCCS-14 N/S Fingertip	043688	(recommended for 800 model)	
&		RMS-14 Pushbutton	187208	See page 6 for kit contents.	
Low-Conductivity Coolant	043810	RMLS-14 Momentary/Maintained	129337	<i>Note: If ordering torch or torch kit for the CE TIGRunner, the QRW water hose quick connects are required.</i>	
(must be ordered in quantities of four)		RHC-14 Hand	242211020		
		Wireless Hand	301582		
		See page 7 for remote descriptions.			

Genuine Miller® Accessories



Runner™ Cart 300244

Designed to accommodate Dynasty 400/800 or Maxstar 400 power sources and a Coolmate™ PRO 4 cooler. Cart features single cylinder rack, foot pedal holder, three cable/torch holders, and two TIG electrode filler holders.



Protective Cover 301920

For Dynasty 400.

301921

For Dynasty 800.

Heavy-duty cover used to protect your welder from damage, wear, and corrosion when not in use.

301921 protective cover shown with runner cart (sold separately).



Coolmate™ PRO 4

301905 CE

301911 CE, quick connect

120/240 V, 50/60 Hz. Industrial 4-gallon cooler for use with water-cooled torches rated up to 600 amps. Designed to integrate with the Dynasty 400/800 and Maxstar 400 power sources.



Low-Conductivity Coolant 043810

Must be ordered in quantities of four. One-gallon recyclable plastic bottle. Miller coolants contain a base of ethylene glycol and

deionized water to protect against freezing to -37 degrees Fahrenheit (-38°C) or boiling to 227 degrees Fahrenheit (108°C). Also contains a compound that resists algae growth.



Performance TIG Gloves

263346 Small

263347 Medium

263348 Large

263349 X-Large

Completely unlined, goat grain leather with triple-padded palm.



Performance TIG/Multitask Gloves

263352 Small

263353 Medium

263354 Large

263355 X-Large

Goat grain leather with dual-padded palm and wool back.



Cut-Resistant TIG Gloves

290401 Small

290402 Medium

290403 Large

290404 X-Large

290411 2X-Large

Protects against cuts and abrasions with an ANSI

A5 cut rating, level 4 puncture and abrasion ratings, and level 3 heat rating.

Automation Interface Connection Kit

278161 Field

Provides control of power source welding parameters through a 28-pin receptacle. The 28-pin receptacle replaces the standard 14-pin receptacle and requires a PLC controller to operate the power source. Ideal for automated equipment integration.

Weld Current Sensor 300179 Field

Detects when work clamp is not connected and prevents expensive damage to disconnect devices and input power cord and wiring.

TIG Torches, Kits and Connectors



Contractor Kit 301549

All-in-one TIG/stick welding kit comes with a Weldcraft™ A-200 TIG torch, RFCS-14 HD foot control, 200-amp stick electrode holder and 300-amp work clamp with 15-foot (4.6 m) cables, flow gauge regulator with 12-foot (3.7 m) gas hose, gas hose coupler, AK2C torch accessory kit and TIG torch connector.



Weldcraft™ A-200 (WP-26) TIG Torch

WP-26-12-R 12 ft.

WP-26-25-R 25 ft.

For Dynasty® 400 only. 200-amp air-cooled torch. Torch body gas valve models are available.

Note: A-200 (WP-26) torches require 195379 connector.



Air-Cooled TIG Torch Connector 195379

50 mm Dinse-style for one-piece A-200 (WP-26) torch air-cooled torch.



W-375 Water-Cooled Torch Kit 301268

Standard torch kit included in Dynasty® 400 Complete package. Kit comes with Weldcraft™ W-375 25-foot (7.6 m) TIG torch with Dinse-style connector, torch cable cover, work clamp with 15-foot (4.6 m) 1/0 cable and Dinse-style connector, flowmeter regulator with gas hose and AK4GL gas lens torch accessory kit.



W-400 (WP-18SC) Water-Cooled Torch Kit 300186

Standard torch kit included in Dynasty® 800 Complete package. Kit comes with Weldcraft™ W-400 25-foot (7.6 m) TIG torch with thread-lock connector, torch cable cover, work clamp with 12-foot (3.7 m) 4/0 cable and thread-lock connector, flowmeter regulator with gas hose and AK18C torch accessory kit.

Genuine Miller® Accessories

TIG Torches, Kits and Connectors (cont.)



Water-Cooled TIG Torch Connector 195377
For Dynasty® 400. 50 mm Dinse-style with water return line. For use with all Weldcraft™ water-cooled torches.



Water-Cooled TIG Torch Connector 225028
For Dynasty 800. 50 mm thread-lock with water return line. For use with all Weldcraft™ water-cooled torches.



Weldcraft™ Gas Hose Quick Connect QRG
Sold individually. Allows for quick connection and removal of torch shielding gas hoses.



Weldcraft™ Water Hose Quick Connect QRW
Sold individually. Allows for quick connection and removal of torch coolant hoses.

Remote Controls and Switches



Wireless Remote Foot Control 301580
For remote current and contactor control. Receiver plugs directly into the 14-pin receptacle of Miller machine. 90-foot (27.4 m) operating range.



RFCS-14 HD Foot Control 301589
Heavy-duty foot pedal current and contactor control provides increased stability and durability from larger base and heavier cord. Includes 20-foot (6 m) cord with plug.



RCC-14 Remote Contactor and Current Control 151086
East/west rotary-motion fingertip control attaches to TIG torch using two hook-and-loop fasteners. Includes 26.5-foot (8 m) cord and 14-pin plug.



RCCS-14 Remote Contactor and Current Control 043688
North/south rotary-motion fingertip control attaches to TIG torch using two hook-and-loop fasteners. Includes 26.5-foot (8 m) cord and 14-pin plug.



RMS-14 On/Off Control 187208
Momentary-contact switch for contactor control. Rubber-covered pushbutton dome switch ideal for repetitive on-off applications. Includes 26.5-foot (8 m) cord and 14-pin plug.



RMLS-14 Switch 129337
Momentary- and maintained-contact rocker switch for contactor control. Push forward for maintained contact and backward for momentary contact. Includes 26.5-foot (8 m) cord and 14-pin plug.



RHC-14 Hand Control 24221020
Miniature hand control for remote current and contactor control. Dimensions: 4 x 4 x 3.25 inches (102 x 102 x 83 mm). Includes 20-foot (6 m) cord and 14-pin plug.



Wireless Remote Hand Control 301582
For remote current and contactor control. Receiver plugs directly into the 14-pin receptacle of Miller machine. 300-foot (91.4 m) operating range.

Extension Cables for 14-Pin Remote Controls
242208025 25 ft. (7.6 m)
242208050 50 ft. (15.2 m)
242208080 80 ft. (24.4 m)

Educational Materials

To order, please call Miller Literature at 866-931-9732 or visit MillerWelds.com/resources/tools.

Gas Tungsten Arc Welding (TIG) Publication 250833

Tungsten

TUNGSTEN	AMP RANGE	2% CERATED (AC/DC)	2% LANTHANATED (AC/DC)
1/16 in. (1.6 mm)	70–150 A	WC116X7	WL2116X7
3/32 in. (2.4 mm)	140–250 A	WC332X7	WL2332X7
1/8 in. (3.2 mm)	225–400 A	WC018X7	WL2018X7
5/32 in. (4.0 mm)	300–500 A	WC532X7	WL2532X7

Ordering Information

EQUIPMENT AND OPTIONS	STOCK NO.	DESCRIPTION	QTY.	PRICE
Dynasty® 400	907950 907950002	Auto-Line™ 208–600 V, 50/60 Hz. 8 ft. power cord Auto-Line™ 380–600 V, 50/60 Hz, CE . 8 ft. power cord		
Dynasty® 400 TIGRunner®	907950001 907950003	Auto-Line™ 208–600 V, 50/60 Hz. 8 ft. power cord (Torch kit, accessories and coolant sold separately) Auto-Line™ 380–600 V, 50/60 Hz, CE . 8 ft. power cord (Torch kit, accessories and coolant sold separately)		
Dynasty® 400 Complete with Wireless Foot Control	951000263	Auto-Line™ 208–600, 50/60 Hz. 8 ft. power cord		
Dynasty® 800	907951 907951002	Auto-Line™ 208–600 V, 50/60 Hz. 8 ft. power cord Auto-Line™ 380–600 V, 50/60 Hz, CE . 8 ft. power cord		
Dynasty® 800 TIGRunner®	907951001 907951003	Auto-Line™ 208–600 V, 50/60 Hz. 8 ft. power cord (Torch kit, accessories and coolant sold separately) Auto-Line™ 380–600 V, 50/60 Hz, CE . 8 ft. power cord (Torch kit, accessories and coolant sold separately)		
Dynasty® 800 Complete with Wireless Foot Control	951000264	Auto-Line™ 208–600, 50/60 Hz. 8 ft. power cord		
Accessories				
Runner™ Cart	300244	See page 6		
Protective Cover	301920 301921	For Dynasty 400 For Dynasty 800		
Coolmate™ PRO 4	301905 301911	120/240 V, 50/60 Hz, CE . <i>Requires coolant</i> 120/240 V, 50/60 Hz, CE . Quick connect. <i>Requires coolant</i>		
TIG Coolant (must be ordered in quantities of four)	043810	1-gallon plastic bottle. Protects against freezing to -37° Fahrenheit (-38°C) or boiling to 227° Fahrenheit (108°C)		
TIG Gloves		See page 6		
Automation Interface Kit	278161	Field installation required. Provides 28-pin automation connections		
Weld Current Sensor	300179	Field installation required. Detects when work clamp is not connected		
Dinse-Style Connector 50 mm (1 male)	042418	Used to connect weld cable to Dinse terminal machine		
Thread-Lock Connectors (2 male)	225029	Used to connect weld cable to Dynasty 800		
Dinse-Style Connector 50 mm (1 male, 1 female)	042419	Used to extend weld cables		
Dinse/Tweco® Adapter	042465	Male Dinse to female Tweco		
Dinse/Cam-Lok Adapter	042466	Male Dinse to female Cam-Lok		
TIG Torches, Kits and Connectors				
Air-Cooled Contractor Kit		See page 6		
Weldcraft™ A-200 (WP-26) TIG Torch		For Dynasty 400 only. <i>Requires 195379 connector</i>		
Water-Cooled Torch Kits		See page 6		
Water-Cooled TIG Torch Connectors	195377 225028	Connects Weldcraft™ water-cooled torches to Dinse-style connector Connects Weldcraft™ water-cooled torches to Dynasty 800 (thread-lock connector included with 800 models)		
Weldcraft™ Quick Connects (sold individually)	QRG QRW	For gas hoses For water hoses		
Tungsten		See page 7		
Remote Controls		See page 7		
Educational Materials		See page 7		

DATE :

TOTAL QUOTED PRICE :

Distributed by:

